





# UL316-96RW

**96W (24 X 4W) - RGBW**

**24VDC**

**Submersible Cast 316L SS**

**Replaceable LEDs**



## Specifications

|                             |   |
|-----------------------------|---|
| <b>Input voltage</b>        | <b>24VDC</b>  |
| <b>Output power</b>         | <b>96 watts (24x4W) 4 in1 RGBW</b>                                    |
| <b>Luminous flux output</b> | <b>100 to 110 lm/W</b>  |
| <b>Rendering Index</b>      | <b>&gt;70rA (warm white)</b>  |
| <b>Beam angle</b>           | <b>recommended 25 degrees - optional 10,45,60,90</b>                  |
| <b>LEDs</b>                 | <b>Replaceable- Internal Driver</b>                                   |
| <b>Material</b>             | <b>Cast 316L STAINLESS STEEL</b>                                      |
|                             | <b>silicone gasket - tempered glass lens</b>                          |
| <b>Face ring</b>            | <b>Standard 'sparkle matt' SS or mirror polish w/ niche</b>           |
| <b>Color options</b>        | <b>RGBW, RGBWW - 4 Channel DMX controllable</b>                       |
| <b>White</b>                | <b>CREE- XPE - 2700K TO 6500K</b>                                     |
| <b>LEDs operating life</b>  | <b>&gt; 50,000 hours - REPLACEABLE LEDs</b>                           |
| <b>IP rating</b>            | <b>IP68 - CERTIFIED SUBMERSIBLE</b>                                   |
| <b>Cable</b>                | <b>9 FEET- SOW 18/5 - longer lengths can be ordered</b>               |
| <b>Dimensions</b>           | <b>Diameter 7 1/2"x 7 1/2"H with yoke</b>                             |
| <b>Certifications</b>       | <b>cULus CSA22.2 no.89 - including swimming pools and splash pads</b> |
| <b>Installation</b>         | <b>Submersible</b>  |

