





# UL316-36

**36W (12 X 3W) - 12VAC/24VDC**  
**SUBMERSIBLE OR DRY**  
**CAST 316L SS**

Cast Stainless Steel - Replaceable LEDs  
 Removable Base, Disc and Yoke  
 Wet or Dry Installation  
 Matte Finish Face Ring or Mirror Polish with Niche



| Specification        | Description  |
|----------------------|--|
| Input voltage        | 12VAC or 24VDC   |
| Output power         | 36 watts (12X3W)   |
| Luminous flux output | 100 to 110 lm/W  |
| Rendering index      | >70rA (warm white)   |
| Beam angle           | 10-15 degrees - optional 25,45,60,90                               |
| LEDs                 | Replaceable - Internal Driver                                      |
| Material             | Cast 316L STAINLESS STEEL<br>silicone gasket - tempered glass lens |
| Face ring            | Standard 'sparkle matt' SS or mirror polish w/ niche               |
| Color option         | RGB-DMX  |
| White                | CREE- XPE - 2700K TO 6500K   |
| LEDs operating life  | > 50,000 hours REPLACEABLE LEDs                                    |
| IP rating            | IP68 - CERTIFIED SUBMERSIBLE OR DRY                                |
| Cable                | 9 FEET- SOW 18/5 - longer lengths can be ordered                   |
| Dimensions           | Diameter 6.89"x 7.2"H with yoke                                    |
| Certification        | cULus CSA22.2 no.89 - including swimming pools and splash pads     |
| Installation         | Submersible or Dry   |

