





UL316-40RW

**10 X 4W - RGBW-DMX - 12VAC/24VDC
SUBMERSIBLE OR DRY
CAST 316L SS**

Cast Stainless Steel - Replaceable LEDs
Removable Base, Disc and Yoke
Wet or Dry Installation
Matte Finish Face Ring or Mirror Polish with Niche



Specification	Description
Input voltage	12VAC or 24VDC
Output power	600-630 mAmps
Luminous flux output	10x 4W (4 in 1) RGBW, RGBWW
Rendering index	>70rA (warm white)
Beam angle	10-15 degrees - optional 25,45,60,90
LEDs	Replaceable - Internal Driver
Material	Cast 316L STAINLESS STEEL silicone gasket - tempered glass lens
Face ring	Standard 'sparkle matt' SS or mirror polish w/ niche
Color option	RGBW(4000K, 6000K) or RGBWW(3000K)
White	CREE- XPE - 2700K TO 6500K
LEDs operating life	> 50,000 hours REPLACEABLE LEDs
IP rating	IP68 - CERTIFIED SUBMERSIBLE OR DRY
Cable	9 FEET- SOW 18/5
Dimensions	Diameter 6.89"x 7.2"H with yoke
Certification	cULus CSA22.2 no.89 UL certified for swimming pools and spas

