





# UL316-96RW

**96W (24 X 4W) - RGBW - 24VDC**  
**SUBMERSIBLE**  
**CAST 316L SS**

Cast Stainless Steel - Replaceable LEDs  
 Removable Base, Disc and Yoke  
 Submersible Installation  
 Matte Finish Face Ring or Mirror Polish with Niche



Specification	Description
Input voltage	24VDC
Output power	96 watts (24x4W) 4 in1 RGBW
Luminous flux output	100 to 110 lm/W
Rendering index	>70rA (warm white)
Beam angle	recommended 25 degrees - optional 10,45,60,90
LEDs	Replaceable - Internal Driver
Material	Cast 316L STAINLESS STEEL silicone gasket - tempered glass lens
Face ring	Standard 'sparkle matt' SS or mirror polish w/ niche
Color option	RGBW, RGBWW - 4 Channel DMX controllable
White	CREE- XPE - 2700K TO 6500K
LEDs operating life	> 50,000 hours REPLACEABLE LEDs
IP rating	IP68 - CERTIFIED SUBMERSIBLE OR DRY
Cable	9 FEET- SOW 18/5 - longer lengths can be ordered
Dimensions	Diameter 7 1/2"x 7 1/2"H with yoke
Certification	cULus CSA22.2 no.89 - including swimming pools and splash pads
Installation	Submersible

