



UL316RS-27

27W (9 X 3W) - 12VAC OR 24VDC
SUBMERSIBLE OR DRY
CAST 316L SS

RGB-DMX or Cree whites
 Solid colors by custom order
 Red, Blue, Green, Amber, WW, NW, CW
 Optional 9 x 4W(4 in 1)- 36W- RGBW-24VDC



Specification

Description

Input voltage	12VAC or 24VDC
Output power	27 watts (9X3W)OPTIONAL 36watt RGBW,RGBWW
Luminous flux output	100 to 110 lm/W
Rendering index	>70rA (warm white)
Beam angle	10-15 degrees - optional 25,45,60,90(25° for RGBW)
LEDs	Replaceable - Internal Driver
Material	Cast 316L STAINLESS STEEL silicone gasket - tempered glass lens
Face ring	Standard 'sparkle matt' SS
Color option	RGB-DMX, RGBW,RGBWW
White	CREE- XPE - 2700K TO 6500K
LEDs operating life	> 50,000 hours REPLACEABLE LEDs
IP rating	IP68 - CERTIFIED SUBMERSIBLE OR DRY
Cable	9 FEET- SOW 18/5 - longer lengths can be ordered
Dimensions	Diameter 9.8"x 2.3"
Certification	cULus CSA22.2 no.89 - including swimming pools and splash pads
Installation	Submersible or Dry

