


# UL316RS-36

**36W (12 X 3W) 12VAC OR 24VDC  
SUBMERSIBLE OR DRY  
CAST 316L SS**

RGB-DMX or Cree whites  
Solid colors by custom order  
Red, Blue, Green, Amber, WW, NW, CW  
Optional 9 x 4W(4 in 1)- 48W- RGBW-24VDC



Specification	Description
Input voltage	12VAC or 24VDC
Output power	36 watts (12X3W)
Luminous flux output	100 to 110 lm/W
Rendering index	>70rA (warm white)
Beam angle	10 -15 degrees - optional 25, 45,60,90
LEDs	Replaceable - Internal Driver
Material	Cast 316L STAINLESS STEEL silicone gasket - tempered glass lens
Face ring	Standard 'sparkle matt' SS
Color option	RGB-DMX
White	CREE- XPE - 2700K TO 6500K
LEDs operating life	> 50,000 hours REPLACEABLE LEDs
IP rating	IP68 - CERTIFIED SUBMERSIBLE OR DRY
Cable	9 FEET- SOW 18/5 - longer lengths can be ordered
Dimensions	Diameter 9.8"x 2.3"
Certification	cULus CSA22.2 no.89 - including swimming pools and splash pads
Installation	Submersible or Dry

