



























































Selection:	316L CAST SS Model Name:	Description:	Dimensions:	Weight:	Options and Add-ons
	  UL316-ORION	5W (1 x 5W) White or RGB, RGBW-DMX 12VAC/24VDC Submersible or DRY Installation	2"MNPT Top x 5 3/16"	2.8kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-60°
	  UL316-9A	9W(3X3W) white or RGB, RGBW - DMX 12VAC/24VDC Submersible or DRY Installation	D 3.2"x 6"H with yoke	2.4kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod
	  UL316-12RW	12W (3 X 4W) RGBW-DMX 12VAC/24VDC Submersible or DRY Installation	D 3.2"x 6"H with yoke	2.4kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod
	  UL316-10RW	10W (1X10W)white or RGBW 12VAC/24VDC Submersible or DRY Installation	D 3.2"x 6"H with yoke		SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-30°-90° Tripod
	  UL316-18	18W (6 X 3W) RGB-DMX 12VAC/24VDC Submersible or DRY Installation	D 4 7/8"x 5 1/2"H with yoke	2.5kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Tripod
	  UL316-24RW	24W (6 X4W) RGBW-DMX 12VAC/24VDC Submersible or DRY Installation	D 4 7/8"x 5 1/2"H with yoke	2.5kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod

 <p>UL316-27</p>	 	<p>27W (9 X 3W} RGB-DMX - WHITE 12VAC/24DC Submersible or DRY Installation</p>	<p>D 5.9"x 7.5"H with yoke</p>	<p>3.2kg</p>	<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Tripod optional</p>
 <p>UL316-32RW</p>	 	<p>32W (8 X4W} RGBW 12VAC/24VDC Submersible or DRY Installation</p>	<p>D 5.9"x 7.5"H with yoke</p>	<p>3.2kg</p>	<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod optional</p>
 <p>UL316-36</p>	 	<p>36W (12 X 3W} RGB-DMX WHITE 12VAC/24VDC Submersible or DRY Installation</p>	<p>D 6.89"x 7.2"H with yoke</p>	<p>3.2kg</p>	<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Tripod optional</p>
 <p>UL316-36-120V</p>	 	<p>36W (12 X 3W} RGB NO DMX-120V OR WHITE Submersible only</p>	<p>D 7 1/2"x 7 1/2"H with yoke</p>		<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Tripod optional</p>
 <p>UL316-40RW</p>	 	<p>40W (10X4W) RGBW-DMX - 24VDC Submersible or DRY Installation</p>	<p>D 6.89"x 7.2"H with yoke</p>		<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod optional</p>
 <p>UL316-54</p>	 	<p>54W (18X 3W} RGB-DMX - White 24VDC Submersible or DRY Installation</p>	<p>D 7 1/2"x 7 1/2"H with yoke</p>	<p>5kg</p>	<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Tripod</p>
 <p>UL316-72RW</p>	 	<p>72W (18X4W} RGBW- 24VDC Submersible only</p>	<p>D 7 1/2"x 7 1/2"H with yoke</p>	<p>5kg</p>	<p>SS NICHE LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod</p>

 <p>UL316-96RW</p>	 	<p>96W (24X4W) RGBW- 24VDC Submersible only</p>	<p>D 7 1/2"x 7 1/2"H with yoke</p>	<p>5.4kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-20°-90° Tripod</p>
 <p>UL316R-24</p>	 	<p>24W (6 X4W) RGBW-DMX 12AC/24DC Submersible or DRY Installation</p>	<p>D 6.3"x 1.4" H Threaded center 1.85"</p>	<p>3kg</p>	<p>Narrow to wide beam lenses Lens- 15°-45° 1"x1 1/2" adapter as pictured</p>
 <p>UL316R-27</p>	 	<p>27W (9 X 3W) RGB-DMX 12AC/24DC Submersible or DRY Installation</p>	<p>D 6.3"x 1.4"H Threaded center 1.85"</p>	<p>3kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens- 10°-45° 1"x1 1/2" adapter</p>
 <p>UL316R-30</p>	 	<p>10x3W (3 in 1)-RGB- DMX-12VAC/24VDC Submersible or DRY Installation</p>	<p>D 6.3"x 1.4"H Threaded center 1.85"</p>	<p>3.5kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-10°-90° 1"x1 1/2" adapter</p>
 <p>UL316R-36</p>	 	<p>36W (12 X 3W) RGB-DMX 12VAC/24VDC Submersible or DRY Installation</p>	<p>D 6.3"x 1.4"H Threaded center 1.85"</p>	<p>3.5kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-10°-45° 1"x1 1/2" adapter</p>
 <p>UL316R-40RW</p>	 	<p>40W (10X4W) RGBW-DMX 24VDC Submersible or DRY Installation</p>	<p>D 6.3"x 1.4"H Threaded center 1.85"</p>	<p>3.5kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-15°-30° 1"x1 1/2" adapter</p>
 <p>UL316R-108</p>	 	<p>108W (36 X 3W) (3 IN 1) RGB-DMX 24VDC Submersible only</p>	<p>D 10.03" x 1.8" H Center 3.15" with 3 bolts</p>	<p>8.0kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-20°-90°</p>
 <p>UL316R-144RW</p>	 	<p>144W (36 X 4W) RGBW- 24VDC Submersible only</p>	<p>D 10.03" x 1.8" H Center 3.15" with 3 bolts</p>	<p>8.0kg</p>	<p>LONGER CABLE Narrow to wide beam lenses Lens-10°-90°</p>

 <p>UL316RS-27</p>	 	27W (9X3W) RGB-DMX 12VAC/24VDC Submersible or DRY Installation	D 9.84" x 2.32" H Center 1.85" with 3 bolts	5.5kg	LONGER CABLE Narrow to wide beam lenses Lens-10°-90° Reduced face ring possible
 <p>UL316RS-36</p>	 	36W (12 X 3W) RGB-DMX 12VAC/24VDC OPTIONAL 48W (12 X 4W) RGBW- 24VDC Submersible or DRY Installation	D 7.24 "x 2.3" H Center 1.85" with 3 bolts		LONGER CABLE Narrow to wide beam lenses Lens-10°-90° slab hanger style face ring
 <p>UL316RS-54</p>	 	54W (18 X 3W) RGB-DMX - 24VDC Submersible or DRY Installation	D 11.4" x 1.88" (full slab) or 8.7" x 1.88" (reduced face ring) Center 2.51" with 3 bolts	6.5kg	LONGER CABLE Narrow to wide beam lenses Lens-10°-90°
 <p>UL316RS-72</p>	 	72W (18X4W) RGBW- 24VDC Submersible only	D 11.4" x 1.88" (full slab) or 8.7" x 1.88" (reduced face ring) Center 2.51" with 3 bolts	6.5kg	LONGER CABLE Narrow to wide- beam lenses Lens-20°-90°
 <p>UL316-Linear</p>	 	27W (9 X 3W) RGB-DMX 12VAC/24VDC Submersible or DRY Installation	L 10.6"x W 3.7"x H 5" to base of yoke	3.7kg	SS NICHE** LONGER CABLE Lens-10°-90°
 <p>UL316-Linear-RW</p>	 	36W (9 X4W) RGBW- 24VDC Submersible or DRY Installation	L 10.6"x W 3.7"x H 5" to base of yoke	3.7kg	SS NICHE** LONGER CABLE Lens-10°-90°
 <p>UL316-Linear-RW-60</p>	 	60W- RGBW OMX- 24VDC Submersible only Installation	L 16" x W 2.75" x H 5" with yoke		SS NICHE** LONGER CABLE Lens-10°-60°
 <p>UL316-RA-120V</p>	 	36W (12 X 3W)-RGB- DMX-120V 48W(12 X 4W)-RGBW- 120V 54W (18 X 3W)-RGB- DMX-120V Submersible only	D 7.95" x 2.7"H plus yoke	5.8kg	SS NICHE LONGER CABLE Narrow to wide beam lenses Optional tripod and/or custom height SS extension post Lens-10°-90°

	  SS Junction Box	6 x 1/2" NPT side outlets can be provided 1" NPT for conduit on bottom Submersible or DRY Installation	VOL. 39 cu. in L 5 1/2" x W 5 1/2" H 3 1/2"	7.6kg	
--	---	--	--	-------	--

All lights are available in white-3000K-6500K.

**Adjustable, rotatable niches are available for most of our lights

Optional glare shields available up to 54W with minimum orders Optional RDM or dimmable on most lights.(Dimmable in 24VDC only at this time)